

# Caudal® Dripline PC700 AS

V1124

## ✂ 0,63 mm

Anti-suction self-compensating drip irrigation

∅ 16 | 22 mm

💧 1,1 | 1,6 | 2,2 | 3,8 l/h

**Water.  
People.  
Future.**




**Caudal**




## TECHNICAL DATA OF THE BRANCH LINE

CAUDAL® Dripline PC700 AS 0,63 mm Ø16 y Ø22

Model			Pres. work max.	KD
	mm	mm	bar	
NCA070016063	15,1	0,63	2,8	0,41
NCA070022063	21,2	0,63	2,8	0,13

## DRIPPER TECHNICAL DATA

The Caudal® PC700 AS 0,63 mm dripline complies with ISO 9261.

	Working pressure range	Water passage dimensions width x depth x length	Filtration area	k	x*	Recommended filtration
l/h	bar	mm	mm			(microns/mesh)
1,1	0,7 - 4,0	0,82 x 0,76 x 139	37,37	1,1	0,0	150/ 100
1,6	0,7 - 4,0	1,06 x 0,85 x 132	37,37	1,6	0,0	150/ 100
2,2	0,7 - 4,0	1,08 x 0,88 x 93,5	37,37	2,2	0,0	120/ 130
3,8	0,7 - 4,0	1,30 x 0,90 x 78,7	37,37	3,8	0,0	120/ 130

\*Within the working pressure range of the dripper dropper.


# Caudal

# MAXIMUM LENGTH OF BRANCH LINE

Minimum pressure in the last dripper of the branch: 0,7 bar.

Ground slope: 0 %.

## CAUDAL® Dripline PC700 AS 0,63 mm Ø 16


Model		Inlet Pressure	Maximum length (m)							
			Dripper spacing (cm)							
			20	30	33	40	50	60	75	100
NCA070016063	l/h	bar								
	1,1	1,0	71	99	107	124	146	167	196	240
		1,5	111	154	166	193	229	262	308	377
		2,0	133	186	201	233	277	317	373	458
		2,8	159	223	240	280	332	381	448	551
	1,6	1,0	56	77	84	97	115	131	154	189
		1,5	86	121	130	151	179	206	242	297
		2,0	104	146	157	183	217	249	293	360
		2,8	125	174	188	219	260	299	352	433
	2,2	1,0	45	63	68	79	93	107	126	154
		1,5	70	98	106	123	146	167	197	242
		2,0	85	118	128	149	177	203	239	294
		2,8	101	142	153	178	212	243	287	353
	3,8	1,0	32	44	48	55	66	75	88	108
		1,5	49	69	74	86	102	117	138	170
		2,0	59	83	89	104	124	142	168	207
		2,8	70	99	107	125	148	171	201	248

# MAXIMUM LENGTH OF BRANCH LINE

Minimum pressure in the last dripper of the branch: 0,7 bar.

Ground slope: 0 %.

## CAUDAL® Dripline PC700 AS 0,63 mm Ø 22

Model		Inlet Pressure	Maximum length (m)							
			Dripper spacing (cm)							
	l/h	bar	20	30	33	40	50	60	75	100
NCA070022063	1,1	1,0	143	194	208	238	278	316	368	446
		1,5	223	303	325	373	437	497	579	703
		2,0	270	367	394	453	530	603	703	854
		2,5	305	415	445	512	601	683	797	969
	1,6	1,0	112	152	163	187	219	249	289	351
		1,5	175	238	255	293	344	390	455	553
		2,0	211	288	309	355	417	474	553	672
		2,5	239	326	349	402	472	537	626	762
	2,2	1,0	91	124	133	153	179	203	236	287
		1,5	142	193	208	239	280	318	371	451
		2,0	172	234	251	289	340	386	451	548
		2,5	194	265	284	327	384	437	511	621
	3,8	1,0	64	87	93	107	126	143	166	202
		1,5	100	136	146	168	197	224	261	318
		2,0	120	164	176	203	239	271	317	386
		2,5	136	186	199	230	270	307	359	437

# LOGISTICAL DATA

Ø	▶◀		⊙	📦 <sup>1</sup>	⊙	⊙	Height	20	40	40   hcpw	🚚	🚚
	mm	mil										
16	0,63	25	600	18,00	0,60	0,18	0,30	280	588	756	468	972
22	0,63	25	500	20,50	0,60	0,18	0,30	280	588	756	468	972

Approximate dimensions. Theoretical calculation.

\*Theoretical weight of the coil without drippers.

## SOME APPLICATIONS:



Vineyard



Stone Fruit



Olive



Gardening and landscaping



Maize



Surface support in RGS



Horticulture



## GUARANTEE

The warranty for our products is limited exclusively to the replacement of defective material, if recognised as such, as far as its manufacture is concerned. The warranty shall not apply if the damage to the product has been caused by improper handling, incorrect installation or improper treatment. Likewise, the guarantee shall not be valid in cases where the material is installed or put into operation for a use other than that for which it was manufactured or designed. Damage and defects caused by external agents such as animals, weather, poor filtering of the installation, clogging of drippers, overpressure, use of aggressive chemical agents, etc. are excluded from this guarantee. The guarantee of our products has a duration of three years from the day of delivery of the material, and claims will only be accepted during these three years of validity.

The data provided in this technical sheet are general information. Extruline Systems S.L. may at any time redesign and/or modify its products, and may change the information contained therein. As in any other document of a general nature, unintentional errors may be found in this document, Extruline Systems S.L. accepts no responsibility for such errors (the technical data sheet valid at the present time is the one you can find at [caudal.es](http://caudal.es)). This document and the information contained in it are the property of Extruline Systems S.L., and may not be copied, used or published, unless expressly authorised by ExtrulineSystems S.L.